

TRX2Sシリーズ拡張ケーブル配線図 (D-sub 15pin)

Alternative cable colours – SUB D 15 connection cable

Number of wires	Wire group	↓	↓	Functionality	Pin at SUB-D connector
		Wire color variant 1	Wire color variant 2		
6	RS232 to Plotter	Green	Green	NMEA out 38400 (-)	15
	RS232 to Plotter	White	White	NMEA out 38400 (+)	7
	RS232 ()	Pink	Red	NMEA in 38400 (-)	10
	RS232 ()	Grey	Black	NMEA in 38400 (+)	2
	RS232 MUX	Brown	Blue	NMEA in 4800, 38400 (-)	11
	RS232 MUX	Yellow	Yellow	NMEA in 4800, 38400 (+)	3
4	Externe Schalter	Green	Green	PAN PAN switch (-)	13
	Externe Schalter	White	Pink	PAN PAN switch (+)	5
	External switches	Brown	Black	Silent switch (-)	12
	External switches	Yellow	Red	Silent switch (+)	4
2	CPA / SART / Anchor	Brown	Black	CPA Alarm (-)	14
	CPA / SART / Anchor	White	Red	CPA Alarm (+)	6
2	RS232 to Plotter	Grey	Grey	NMEA Ausgang 4800, 38400 (-)	9
	RS232 to Plotter	Yellow	Yellow	NMEA Ausgang 4800, 38400 (+)	1

Note:

(A) **(B)**

お手元のD-sub15pinケーブルに青い配線がある場合は**(B)**の配線図を参考にしてください。